

GROWATT THOR Smart EV Charger

THOR 07AS-SE/PE-V1 (Single Phase)

- Compatible with all branded EV
- Integration in existing & new-installed PV system
- Charge EV with 100% renewable energy by surplus solar power
- APP smart control & smart scheduling
- IP65 design for indoor or outdoor use



GROWATT

www.ginverter.com

P O W E R
- I N G O
T O M O -
R R O W O

Datasheet	THOR 07AS-PE		THOR 07AS-SE	
Input & Output				
Input voltage	230V AC			
Input frequency	50/60Hz			
Output voltage	230VAC			
Max. output power	7KW		7KW	
Max. output current	32A		32A	
Charging interface type	IEC 62196-2, Type 2			
Connection	Plug		Socket	
Cable Length	5m		/	
Protection				
Over voltage protection	Yes			
Under voltage protection	Yes			
Over load protection	Yes			
Short circuit protection	Yes			
Earth leakage protection	6mA DC fault current protection			
Over-temp protection	Yes			
Lightning protection	Yes			
Function and Accessory				
Ethernet/WIFI/4G	Yes/Yes/Opt			
LCD	No			
RCD	6mA DC fault current protection			
Charge activation	APP/Plug&Charge/RFID		APP/Plug&Charge/RFID	
LED Indicator light	Yes			
Emergency stop button	Yes			
Multiple workmodes	Fast/ PV Linkage/ Off-peak/ Load balancing			
Communication Protocol	OCPP 1.6			
MID meter	Opt			
Installation	Floor/wall-mounting			
General				
Protection degree	IP65			
Environment temperature	-25°C ~ +50°C			
Relative humidity	5-95% non-condensing			
Maximum altitude	<2000m			
Cooling	Natural cooling			
Standby power consumption	< 8W			
Dimension (W/H/D)	240/380/164mm			
Weight	5kg		3kg	
Wall-mounting bracket/ Ground-mounting pole	Yes/Opt			
UKCA, CE (LVD&EMC, EN 61851-1, EN61851-22, EN61000-6-3, EN61000-6-1), IEC62196				